TW56D0T-IRF
HD1080p IR Turret Camera





主要特色

- 2 百萬畫素高性能 CMOS
- 1920 x 1080 解析度
- 日夜模式切換
- 智慧紅外線
- 夜視有效距離達 20 公尺
- 四合一影像輸出（TVI/AHD/CVI/CVBS）
- IP66 防水等級


產品規格

攝影機	
感光元件	2MP CMOS image sensor
訊號格式	PAL / NTSC
有效像素	1920 (H) × 1080 (V)
最小照度	0.01 Lux (F1.2，AGC ON)，紅外線啟用：0 Lux
快門時間	1/30 ~ 1/50,000 秒
鏡頭	2.8mm / 3.6mm / 6.0mm
	視角: 103° (2.8 mm) / 82.2° (3.6 mm) / 54° (6.0 mm)
鏡頭安裝	M12
日夜切換	機械式紅外線濾光片自動切換
角度範圍	水平: 0° ~ 360° / 垂直: 0° ~ 75° / 旋轉: 0° ~ 360°
同步掃描	內部同步掃描
影像張數	1080p @ 30fps
影像輸出	類比高清影像輸出 x 1
訊號雜訊比	>62 dB
其他	
工作環境	溫度：–40 °C ~ 60 °C (–40 °F ~ 140 °F)，濕度: 90%以下
電源	12V DC±15%
耗電量	最大 4W
防水等級	IP66
紅外線範圍	可達 20 公尺
外型尺寸	Φ 89.9 mm × 70.1 mm (3.54" × 2.76")
重量	280g (0.62 lb.)

產品型號

TW56D0T–IRF

外型尺寸



配件



DS-1272ZJ-110-TRS

壁掛支架



DS-1275ZJ

直桿安裝支架



DS-1276ZJ

轉角安裝支架



DS-1H18

雙絞線頭



X41T

攝影機影像測試螢幕



DS-1280ZJ-XS

防水收納底座

Distributed by

Headquarters
No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
overseasbusiness@hikvision.com

Hikvision USA
T +1-909-895-0400
sales.usa@hikvision.com

Hikvision India
T +91-22-28469900
sales@pramahikvision.com

Hikvision UK
T +44-1628-9021-4
support.uk@hikvision.com

Hikvision Europe
T +31-23-5542770
saleseuro@hikvision.com

Hikvision Italy
T +39-0438-6902
info.it@hikvision.com

Hikvision Singapore
T +65-6684-4718
sg@hikvision.com

Hikvision Middle East
T +971-4-8816086
salesme@hikvision.com

Hikvision France
T +33(0)1-85-330-444
info.fr@hikvision.com

Hikvision Oceania
T +61-2-8599-4233
salesau@hikvision.com

Hikvision Russia
T +7-495-669-67-99
saleru@hikvision.com

Hikvision Spain
T +34-91-737-16-55
info.es@hikvision.com

Hikvision Hong Kong
T +852-2151-1761

Hikvision Poland
T +48-22-460-01-50
poland@hikvision.com

© Hikvision Digital Technology Co., Ltd. 2015 | Data subject to change without notice |