

## PS-I3264P

# 六埠全千兆網路供電工業型網路交換器



Product Name	4GE+2GE Full Gigabit Industrial Ethernet PoE Switch
Interface	6x 10/100/1000M copper RJ45 ports,
PoE Specification	PoE Standard: IEEE802.3af/at
	Single PoE Port Power Output: Max 30W
	4 PoE port auto detect af/at devices
	PoE Port Output Voltage: DC48-57V
	Power Pin Assignment:1,2(+)/3,6(-) for default,
Forwarding Mode	Store-and-forward
Performance Specification	Bandwidth: 16Gbps Packet Buffer Memory:2M Packet Forwarding Rate:8.93Mpps Address Table: 8K MTBF: 539608 hours
Standards Compliance	IEEE802.3: CSMA/CD; IEEE802.3i: 10Base-T; IEEE802.3u: 100Base-T; IEEE802.3ab: 1000Base-T;

	IEEE802.3z: 1000Base-LX
LED Indicators	Power: PWR; Link; PoE;L/A
Power	Removable industrial 5-pin terminal block
Dimension / Weight	119*100*30mm / 0.35Kg
Working Environment	<p>Working Temperature: -40 ~ 80°C;</p> <p>Storage Temperature: -40 ~ 85°C;</p> <p>Working Humidity: 5% ~ 95%(non-condensing);</p> <p>Storage Humidity: 5% ~ 95%(non-condensing);</p> <p>Working high: Altitude of 3000 m(10,000ft);</p> <p>Storage high: Altitude of 3000 m(10,000ft);</p>
Certification	<p>CE mark, commercial;</p> <p>FCC Part 15 Class B;</p> <p>VCCI Class B</p> <p>EN 55022 (CISPR 22), Class B;</p> <p>CE Mark, commercial;</p> <p>CE/LVD EN60950;</p>