

## PS-20844D

# 八埠超高速智慧網路供電交換器



固定端口	8 個 10/100/1000M POE PORT
	2 組 100/1000 PORT 及 2 組千兆 SFP
POE	支援 802.3 af/at
Reset 鍵	1 個
指示燈號	PWR 電源, 1~8POE, 9~12 UPIINK
交換內容	56 Gbps 無阻塞
轉發率	14.44Mpps
CPU 頻率	500MHZ DDR :1G
RAM	1M
MAC	8K
包緩衝區	4.1M
FLASH	8M
傳輸方式	存儲轉發
端口特性	10/100/1000M 自動偵測 MDI/MDI-X 全雙工自動偵測
雙絞線特性	10MBASE-T cat 3.4.5 UTP (250M)
	100 MBASE-T cat 5 UTP (100M)
	100 MBASE-T cat 6 UTP (1000M)
工作溫度	-20°C~52°C
儲存溫度	-40°C~70°C
工作濕度	10%~90%無凝結
儲存濕度	5%~95%無凝結
防雷等級	4KV
防護等級	IP30
裸機尺寸	250(L)*150(W)*45(H)mm

輸入電壓	AC 90~265V 50/60HZ
認證	CE ,FCC part 15 classB , CE/LVD EN60950
整機功耗	150W
電壓	110-240V 50/60Hz
選購	360W電源供應器、機櫃套件、搭配 NVR 主機可擴充智慧重啟功能

## FIBER MODULE LIST

	Model	Description	Unit
1.25G Fiber Module	850MM-LC	1.25G SFP module, dual LC interface. Multi mode dual fiber, 850nm. Transmission distance is 550meters. Working voltage is 3.3V. Support DDM and hot plugging.	PC
	1310SM-LC	1.25G SFP module, dual LC interface. Single mode dual fiber, 1310nm. Transmission distance is 20km. Working voltage is 3.3V. Support DDM and hot plugging.	PC
	1315A-LC	1.25G SFP module, single LC interface. Single mode single fiber, 1310nm(transmitter), 1550nm(receiving). Transmission distance is 20km. Working voltage is 3.3V. Support DDM and hot plugging.	PC
	1315B-LC	1.25G SFP module, single LC interface. Single mode single fiber, 1550nm(transmitter), 1310nm(receiving). Transmission distance is 20km. Working voltage is 3.3V. Support DDM and hot plugging.	PC
	1315A-SC	1.25G SFP module, single SC interface. Single mode single fiber, 1310nm(transmitter), 1550nm(receiving). Transmission distance is 20km. Working voltage is 3.3V. Support DDM and hot plugging.	PC
	1315B-SC	1.25G SFP module, single SC interface. Single mode single fiber, 1550nm(transmitter), 1310nm(receiving). Transmission distance is 20km. Working voltage is 3.3V. Support DDM and hot plugging.	PC
Ethernet Module	SFP/TP	1.25G Ethernet module , cover SFP to 10/100/1000M RJ45 port	PC